Material Characteristics

HARDSCAPE
Inspire. Select. Supply.

Commercial Name: Kobra Green
Stone Type: Green / Granite
Place of Origin: Fujian / China

Characteristics	Value	Test standard
Flexural Strength (MPa) LEV	20.20	BS EN 12372:2006
Flexural Strength freeze / thaw resistance before and after (MPa) MEAN	24.6 / 26.1	BS EN 12371:2010
Compressive Strength (MPa) LEV	123.00	BS EN 1926:2006
Compressive Strength freeze / thaw resistance before and after (MPa) MEAN	141 / 142	BS EN 12371:2010
Slip Resistance	Flamed: 71 (wet) BH: 81 (wet)	BS EN 14231:2003
Water Absorption (%)	0.11	BS EN 13755:2008
Wide Wheel Abrasion (mm)	19.1	BS EN 14157:2004
Open Porosity (%)	0.3	BS EN 1936:2006
LRV	19 (BH)	BS EN 84369:2008

Ethical Trading Initiative
Respect for workers worldwide

CfA Centre for Assessment ISO 9001 06/2335

CfA Centre for Assessment ISO 14001 16/4466

Federation Stone Great Britain

Hardscape North (Registered office) Eagley House, Deakins Business Park, Egerton, Bolton, Lancashire, BL7 9RP
Hardscape Midlands - Sales - 1st & 2nd Floor, Guild House, Packwood Court, Guild Street, Stratford Upon Avon, CV37 6RP
Hardscape Midlands - Production - Unit 25, Long Marston Industrial Estate, Long Marston, Stratford Upon Avon, CV37 8QR
Hardscape South - 59 Warwick Way, Pimlico, London, SW1V 1QR
Hardscape Scotland - 44 Charlotte Square, Edinburgh, EH2 4HQ
Hardscape Ireland - Building C The Studios, 89 Holywood Road, Belfast, BT4 3BD
Telephone 01204 565 500 **Email** enq@hardscape.co.uk

www.hardscape.co.uk