



Test Data & Material Characteristics

Hardscape Products Limited

Date of Certificate

25

01/12/2025

Commercial Name: Azul Noche
Stone Type: Dark Grey, Black / Granite
Place of Origin: Ávila / Spain
Density (Kg/m3): 2750



Characteristics	Value	Test standard
Flexural Strength (MPa) LEV	14.90	BS EN 12372:2006
Flexural Strength freeze / thaw resistance before and after (MPa) MEAN	14.9 / 14.1	BS EN 12371:2010
Compressive Strength (MPa) LEV	141.00	BS EN 1926:2006
Compressive Strength freeze / thaw resistance before and after (MPa) MEAN	NPD	BS EN 12371:2010
Slip Resistance	NPD (Textured Surface)	BS EN 14231:2003
Water Absorption (%)	0.20	BS EN 13755:2008
Wide Wheel Abrasion (mm)	16	BS EN 14157:2004
Open Porosity (%)	NPD	BS EN 1936:2006
PPV (Before/After Polishing)	NPD	BS EN 7932:2003
Light Reflectance Value (LRV) %	25.86 (Flamed), 25.61 (Bush-Hammered)	BS EN 84369:2008

All tests conform to the specific standard requirements and test methods for the material types as detailed below:

Signed:

BS EN 1341:2012

Slabs of natural stone for external paving



HARDSCAPE
PRODUCTS



Federation
stone
Great Britain

Hardscape Products Ltd., Eagley House, Deakins Business Park, Egerton, Bolton, Lancashire, BL7 9RP

Telephone 01204 565 500

Email enq@hardscape.co.uk

Website: <https://hardscape.co.uk/>