

	Test Data & Material Characteristics	
	Hardscape Products Ltd.	Date of Certificate
	25	11/12/2025

BS EN 1338:2003 - Precast Concrete Paving Blocks Requirements and Test Methods		
Commercial name: Ecogranite Aquaflow		
Place of manufacture: UK		
Uses: Internal and external flooring and / or roof covering		
Declared Performance		
Characteristics	Value	Testing Method Standard
Reaction to Fire	A1	BS EN 1339:2003 (5.3.7.1)
External Fire Performance	NPD	BS EN 1339:2003 (5.3.7.2)
Emission of asbestos	No ACMs Present	BS EN 1339:2003 (4.2)
Breaking strength	3.6MPa	BS EN 1339:2003 (5.3.3.1&2)
Slip / skid resistance	NPD (textured surface)	BS EN 1339:2003 (5.3.5.1&2)
Thermal Conductivity	NPD	BS EN 1339:2003 (5.3.7)/ EN 13369
Durability	Satisfactory	BS EN 1339:2003 (5.3.3.3)
Light Reflectance Value	NPD	BS 8493:2008+A1:2010

All tests conform to the specific standard requirements and test methods for the material types as detailed above:	Signed:	
Products are offered in line with the requirements of Attestation Level 4 as designated under the Construction Products Regulations (2011) Annex V. Type testing, routine testing and Factory Production Control documents have been developed and issued for this series of products.		

Hardscape Products Ltd., Eagley House, Deakins Business Park, Egerton, Bolton, Lancashire, BL7 9RP

Telephone 01204 565 500

Email enq@hardscape.co.uk

Website: <https://hardscape.co.uk/>