



Test Data & Material Characteristics

Hardscape Products Limited

Date of Certificate

25

01/12/2025

Commercial Name: Rojo Moncayo
 Stone Type: Red / Sandstone
 Place of Origin: Castellon / Spain
 Density (Kg/m3): 2420



| Characteristics | Value | Test standard |
|---|----------------|------------------|
| Flexural Strength (MPa) Mean | 10.5 | BS EN 12372:2006 |
| Flexural Strength freeze / thaw resistance before and after (MPa) MEAN | 10.5 / 10.6 | BS EN 12371:2010 |
| Compressive Strength (MPa) Mean | 131 | BS EN 1926:2006 |
| Compressive Strength freeze / thaw resistance before and after (MPa) MEAN | 131 / 145 | BS EN 12371:2010 |
| Slip Resistance | Unpolished: 90 | BS EN 14231:2003 |
| Water Absorption (%) | 2.00 | BS EN 13755:2008 |
| Wide Wheel Abrasion (mm) | 20 | BS EN 14157:2004 |
| Open Porosity (%) | 8.1 | BS EN 1936:2006 |
| PPV (Before/After Polishing) | NPD | BS EN 7932:2003 |
| Light Reflectance Value (LRV) % | NPD | BS EN 84369:2008 |

All tests conform to the specific standard requirements and test methods for the material types as detailed below:

Signed:

BS EN 1341:2012

Slabs of natural stone for external paving



Hardscape Products Ltd., Eagle House, Deakins Business Park, Egerton, Bolton, Lancashire, BL7 9RP

Telephone 01204 565 500

Email enq@hardscape.co.uk

Website: <https://hardscape.co.uk/>