

## Material Characteristics



Commercial Name: Angola Black  
 Stone Type: Dark Grey, Black / Granite  
 Place of Origin: Angola / Africa  
 Density (Kg/m3): 2840



Characteristics	Value	Test standard
Flexural Strength (MPa) LEV	19.50	BS EN 12372:2006
Flexural Strength freeze / thaw resistance before and after (MPa) MEAN	19.5 / 19.0	BS EN 12371:2010
Compressive Strength (MPa) LEV	201.00	BS EN 1926:2006
Compressive Strength freeze / thaw resistance before and after (MPa) MEAN	x	BS EN 12371:2010
Slip Resistance	Honed: 19 (wet), 59 (dry)	BS EN 14231:2003
Water Absorption (g/m2/s2)	0.10	BS EN 13755:2008
Wide Wheel Abrasion (mm)	16.1	BS EN 14157:2004
Open Porosity (%)	0.3	BS EN 1936:2006
PPV (Before/After Polishing)	x	BS EN 7932:2003
Light Reflectance Value (LRV) %	11.9 (Flamed), 15.4 (Bush-Hammered)	BS EN 84369:2008



Hardscape Products Ltd., Eagley House, Deakins Business Park, Egerton, Bolton, Lancashire, BL7 9RP

Telephone 01204 565 500 Email [enq@hardscape.co.uk](mailto:enq@hardscape.co.uk)

[www.hardscape.co.uk](http://www.hardscape.co.uk)