

Material Characteristics



Commercial Name: Brown Mica
 Stone Type: Buff / Granite
 Place of Origin: Coimbra / Portugal
 Density (Kg/m3): 2610



Characteristics	Value	Test standard
Flexural Strength (MPa) LEV	15.40	BS EN 12372:2006
Flexural Strength freeze / thaw resistance before and after (MPa) MEAN	x	BS EN 12371:2010
Compressive Strength (MPa) LEV	147.00	BS EN 1926:2006
Compressive Strength freeze / thaw resistance before and after (MPa) MEAN	x	BS EN 12371:2010
Slip Resistance	Unpolished: 60	BS EN 14231:2003
Water Absorption (g/m2/s2)	0.40	BS EN 13755:2008
Wide Wheel Abrasion (mm)	22.9	BS EN 14157:2004
Open Porosity (%)	x	BS EN 1936:2006
PPV (Before/After Polishing)	x	BS EN 7932:2003
Light Reflectance Value (LRV) %	49.5 (Flamed), 38.5 (Bush-Hammered)	BS EN 84369:2008



**Ethical
Trading
Initiative**



**Ethical
Stone
Register**



**Federation
stone
Great Britain**

Hardscape Products Ltd., Eagleley House, Deakins Business Park, Egerton, Bolton, Lancashire, BL7 9RP

Telephone 01204 565 500 Email enq@hardscape.co.uk

www.hardscape.co.uk