


Natural Stone / Granite / Scotland / Argyle | Whinstone

Argyle Whinstone

A hard, attractive and versatile quartz-dolerite material used for hundreds of years. It is suitable for paving as well as for kerbs, setts, channels and walling.

SPECIFICATION	SKU: GRA-SCO-ARG-002	
Material	Granite	
Finish	Flamed, Sawn	
Density	-	2990 kg/m ³
GWP (total) kgCO ₂ e	ISO 14025 / EN 15804	-
Compressive Strength	BS EN 1926:2006	209 Mpa
Compressive Strength (Freeze/Thaw Resistance)	BS EN 1926:2006	209 / 190 Mpa
PPV (Before/After)	BS EN 7932:2003	NPD
Flexural Freeze/Thaw	BS EN 12371:2010	23.9 / 22.9 MPa
Flexural Strength	BS EN 12372:2006	25 MPa
Light Reflectance Value	BS EN 84369:2008	Flamed 9.1 : Sawn 13.2 LRV
Open Porosity	BS EN 1936:2006	0.5%
Slip Resistance	BS EN 13036-4, BS 7976	Flamed 71 (wet), 89 (dry) SRV/USRV
Water Absorption	BS EN 13755:2008	0.3%
Abrasion Resistance	BS EN 14157:2004	17mm



Flamed



Specification & technical data aligns with our most recent testing, but is indicative and should be treated as such. Images are for illustrative purposes only, exact colours may vary.