

Natural Stone / Sandstone / England / Crosland Hill | Multi

Crosland Hill

Multi

Selected to include brown shade and swirls combining with blue and grey tones to produce an attractive brindle appearance when laid.

SPECIFICATION	SKU: SAN-ENG-CHI-014	
Material	Sandstone	
Finish	Diamond Sawn, Fine Rubbed, Sawn	
Density	-	2406 kg/m ³
GWP (total) kgCO ₂ e	ISO 14025 / EN 15804	0.045 per kg
Compressive Strength	BS EN 1926:2006	79 MPa LEV
Compressive Strength (Freeze/Thaw Resistance)	BS EN 1926:2006	NPD
PPV (Before/After)	BS EN 7932:2003	NPD
Flexural Freeze/Thaw	BS EN 12371:2010	15.0 / 13.0 MPa Mean
Flexural Strength	BS EN 12372:2006	11.9 MPa LEV
Light Reflectance Value	BS EN 84369:2008	Sawn 37.2 : Shotblasted 33.1 LRV
Open Porosity	BS EN 1936:2006	9.59%
Slip Resistance	BS EN 13036-4, BS 7976	Diamond Sawn 79 (wet), 101 (dry) : Sawn 84 (wet), 95 (dry) SRV/USRV
Water Absorption	BS EN 13755:2008	2.87%
Abrasion Resistance	BS EN 14157:2004	16.5mm



Specification & technical data aligns with our most recent testing, but is indicative and should be treated as such. Images are for illustrative purposes only, exact colours may vary.



Diamond Sawn