

Natural Stone / Granite / England / De Lank | Silver Grey

De Lank

Silver Grey

Known for its beauty, durability and strength, and has been used to create some of the UK's most famous landmarks.



Flamed

SPECIFICATION	SKU: GRA-CHI-ROY-026	
Material	Granite	
Finish	Bush Hammered, Flamed, Honed, Polished, Sandblasted, Sawn	
Density	-	-
GWP (total) kgCO2e	ISO 14025 / EN 15804	-
Compressive Strength	BS EN 1926:2006	-
Compressive Strength (Freeze/Thaw Resistance)	BS EN 1926:2006	-
PPV (Before/After)	BS EN 7932:2003	-
Flexural Freeze/Thaw	BS EN 12371:2010	-
Flexural Strength	BS EN 12372:2006	-
Light Reflectance Value	BS EN 84369:2008	-
Open Porosity	BS EN 1936:2006	0.88%
Slip Resistance	BS EN 13036-4, BS 7976	Bush Hammered 86 (wet), 91 (dry) : Flamed 73 (wet), 83 (dry) SRV/USRV
Water Absorption	BS EN 13755:2008	0.3%
Abrasion Resistance	BS EN 14157:2004	19.3mm



Specification & technical data aligns with our most recent testing, but is indicative and should be treated as such. Images are for illustrative purposes only, exact colours may vary.