

Natural Stone / Sandstone / England / Umber | Woodkirk

Umber

Woodkirk

Featuring a grey/buff colour it is both aesthetically pleasing and high quality. An extremely versatile material used in all types of applications.

SPECIFICATION	SKU: SAN-ENG-UMB-004	
Material	Sandstone	
Finish	Bush Hammered / Shotblasted, Honed, Sawn, Tumbled	
Density	-	2330 kg/m ³
GWP (total) kgCO ₂ e	ISO 14025 / EN 15804	-
Compressive Strength	BS EN 1926:2006	66 Mpa
Compressive Strength (Freeze/Thaw Resistance)	BS EN 1926:2006	73 / 67 Mpa
PPV (Before/After)	BS EN 7932:2003	Sawn 88/71 PPV
Flexural Freeze/Thaw	BS EN 12371:2010	11.2 / 11.4 MPa
Flexural Strength	BS EN 12372:2006	9.7 MPa
Light Reflectance Value	BS EN 84369:2008	Sawn 29.8 LRV
Open Porosity	BS EN 1936:2006	13.8%
Slip Resistance	BS EN 13036-4, BS 7976	Sawn 71 (wet), 74 (dry) SRV/USRV
Water Absorption	BS EN 13755:2008	4.4%
Abrasion Resistance	BS EN 14157:2004	25mm



Sawn



Specification & technical data aligns with our most recent testing, but is indicative and should be treated as such. Images are for illustrative purposes only, exact colours may vary.