

Civils & Highways / Active Travel Kerbs / Highway / Highway 130-150

Highway 130-150x160 VB


130-150x160 VB | Radius | L-960 | External | 8m | Half-Battered | VB

SPECIFICATION

Highway 130-150x160 VB | 130-150x160 VB | Radius | L-960 | External | 8m | Half-Battered | VB

SKU: ATK-HWA-002-5223

Material	Concrete, Kellen
Finish	Standard Wet Cast, Lavarò
Size	130-150(w) x 160(d) x 960(l)
Weight Per Unit	50.85kg
Manufacturing Standard	BS EN 1340:2003
Density	2350 kg/m ³
GWP (total) kgCO ₂ e	5.42 kgCO ₂ e/unit
Dutch Ref.	TROTTOIRBOCHTBANDEN-13-15x16xL96-8m-VB
Type	Radius External
End Style	VB
Profile	130-150x160
Position	-
Face	Half-Battered
Face Angle	81°
Return Angle	-
Radius	8m
Number per 360	52
Slope Angle	-
Slope Gradient	-



Active Travel Kerbs are available in a range of colours, finishes and materials.

View product online at : <https://hardscape.co.uk/product/Highway-130-150x160-VB-130-150x160-VB-Radius-L-960-External-8m-Half-Battered-VB/>

Specification & technical data is indicative and subject to change. Images are for illustrative purposes only, details may vary. Some data may vary according to colour / material / finish variation.