Civils & Highways / Active Travel Kerbs / Highway / Highway 130-150

Highway 130-150x250 HD

130-150x250 HD | Transition | to 40-120x170 | L-1000 | Half-Battered | HDHD

SPECIFICATION

Highway 130-150x250 HD | 130-150x250 HD | Transition | to 40-120x170 | L-1000 | Half-Battered | HDHD

SKU: ATK-HWA-005-5500

Material	Concrete, Kellen
Finish	Standard Wet Cast, Lavaro
Size	130-150(w) x 250(d) x 1000(l)
Weight Per Unit	76kg
Manufacturing Standard	BS EN 1340:2003
Density	2350 kg/m³
GWP (total) kgCO2e	8.1 kgCO2e/unit
Dutch Ref.	VERLOOPBANDEN-13-15x25_4-12x17xL100-HD
Type	Transition
End Style	HDHD
Profile	130-150x250
Position	-
Face	Half-Battered_Splay
Face Angle	81°
Return Angle	-
Radius	-
Number per 360	-
Slope Angle	-
Slope Gradient	-



Active Travel Kerbs are available in a range of colours, finishes and materials.

Specification & technical data is indicative and subject to change. Images are for illustrative purposes only, details may vary. Some data may vary according to colour / material / finish variation.