

Civils & Highways / Active Travel Kerbs / Highway / Highway 180-200


Highway 180-200x120 VB

180-200x120 VB | Radius | L-785 | External | 1.5m | Half-Battered | VB

SPECIFICATION

Highway 180-200x120 VB | 180-200x120 VB | Radius | L-785 | External | 1.5m | Half-Battered | VB
SKU: ATK-HWC-002-5661

Material	Concrete, Kellen
Finish	Standard Wet Cast, Optiflex, Lavarø
Size	180-200(w) x 120(d) x 785(l)
Weight Per Unit	37.9kg
Manufacturing Standard	BS EN 1340:2003
Density	2350 kg/m ³
GWP (total) kgCO ₂ e	4.04 kgCO ₂ e/unit
Dutch Ref.	TROTTOIRBOCHTBANDEN-18-20x12xL78.5-1.5m-VB
Type	Radius External
End Style	VB
Profile	180-200x120
Position	-
Face	Half-Battered
Face Angle	81°
Return Angle	-
Radius	1.5m
Number per 360	12
Slope Angle	-
Slope Gradient	-



Active Travel Kerbs are available in a range of colours, finishes and materials.

 View product online at : <https://hardscape.co.uk/product/Highway-180-200x120-VB-180-200x120-VB-Radius-L-785-External-1-5m-Half-Battered-VB/>