

Civils & Highways / Active Travel Kerbs / Highway / Highway 180-200


Highway 180-200x160 VB

180-200x160 VB | Radius | L-960 | Internal | 8m | Half-Battered | VB

SPECIFICATION

Highway 180-200x160 VB | 180-200x160 VB | Radius | L-960 | Internal | 8m | Half-Battered | VB
SKU: ATK-HWC-004-5722

Material	Concrete, Kellen
Finish	Standard Wet Cast, Optiflex, Lavarò
Size	180-200(w) x 160(d) x 960(l)
Weight Per Unit	69.01kg
Manufacturing Standard	BS EN 1340:2003
Density	2350 kg/m ³
GWP (total) kgCO ₂ e	7.35 kgCO ₂ e/unit
Dutch Ref.	TROTTOIRBOCHTBANDEN-18-20x16xL96-8m-VB-inw
Type	Radius Internal
End Style	VB
Profile	180-200x160
Position	-
Face	Half-Battered
Face Angle	81°
Return Angle	-
Radius	8m
Number per 360	52
Slope Angle	-
Slope Gradient	-



Active Travel Kerbs are available in a range of colours, finishes and materials.

 View product online at : <https://hardscape.co.uk/product/Highway-180-200x160-VB-180-200x160-VB-Radius-L-960-Internal-8m-Half-Battered-VB/>

Specification & technical data is indicative and subject to change. Images are for illustrative purposes only, details may vary. Some data may vary according to colour / material / finish variation.